

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 7739-10 (1975): Code of Practice for Preparation of Metallographic Specimens, Part 10: Tin and its alloys and their examination [MTD 22: Metallography and Heat Treatment]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrihari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS : 7739 (Part X) - 1975

Indian Standard

CODE OF PRACTICE FOR PREPARATION OF METALLOGRAPHIC SPECIMENS

PART X TIN AND ITS ALLOYS AND THEIR EXAMINATION

UDC 620.182.2:669.6



© Copyright 1976

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Price Rs 5.00 **Gr 2**

June 1976

*Indian Standard*CODE OF PRACTICE FOR PREPARATION
OF METALLOGRAPHIC SPECIMENS**PART X TIN AND ITS ALLOYS AND
THEIR EXAMINATION**

Metallography and Heat-Treatment Sectional Committee, SMDC 27

Chairman

SHRI K. V. CHINNAPPA

Representing

International Nickel (India) Pvt Ltd, Bombay

Members

SHRI M. ANJANEYULU

Mining & Allied Machinery Corporation Limited,
DurgapurSHRI N. V. RAGHWAN (*Alternate*)

SHRI N. C. BAGCHI

National Test House, Calcutta

SHRI S. N. BANERJEE

Indian Institute of Metals, Calcutta

SHRI S. S. BHATNAGAR

National Metallurgical Laboratory (CSIR),
Jamshedpur

DR S. K. CHATTERJEE

Guest, Keen, Williams, Ltd, Howrah

SHRI S. K. BASU (*Alternate*)

SHRI DASARATHA

The Mysore Iron & Steel Ltd, Bhadravati

SHRI B. HARIDASACHAR (*Alternate*)

SHRI D. M. DAVAR

Premier Automobiles Ltd, Bombay

SHRI A. T. BORATE (*Alternate*)

DEPUTY DIRECTOR (MET)-3, Ministry of Railways

RDSO

CHEMIST & METALLURGIST (*Alternate*)

SHRI A. K. GUHA

Directorate General of Supplies & Disposals
(Inspection Wing), New DelhiSHRI P. C. MUSTAFI (*Alternate*)

SHRI H. A. JAISINGHANI

Mahindra & Mahindra Ltd, Bombay

SHRI A. R. RANADIVE (*Alternate*)

SHRI M. L. KATYAL

Bajaj Auto Ltd, Pune

DR D. M. LAKHIANI

Indian Iron & Steel Co Ltd, Burnpur

SHRI D. R. DASGUPTA (*Alternate*)

SHRI N. MAJUMDAR

Indian Aluminium Co Ltd, Calcutta

SHRI S. N. BOSE (*Alternate*)

DR G. MUKHERJEE

Hindustan Steel Ltd, Ranchi

SHRI D. K. BAGCHI (*Alternate*)

SHRI A. PADMANABAN

Ashok Leyland Ltd, Madras

(Continued on page 2)

© Copyright 1976

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members

SHRI B. M. PAI

SHRI S. A. MALWADE (*Alternate*)

DR P. S. PATTIHAL

SHRI J. C. KAPOOR (*Alternate*)

SHRI N. M. RAJU

SHRI B. RAMA KRISHNA

SHRI J. NAGESH BHAT (*Alternate*)

SHRI V. RAMA SWAMY

SHRI R. H. G. RAU

SHRI G. G. SAHA

SHRI H. N. SINGH

DR L. R. VAIDYANATH

SHRI V. V. VIRBHADRAYYA

SHRI K. L. CHATTERJEE (*Alternate*)

SHRI SUBHASH WADHAVAN

SHRI C. R. RAMA RAO,

Director (Struc & Met)

Representing

The Alloy Steel Producers' Association of India,
Bombay

Tata Engineering & Locomotive Co Ltd, Jamshedpur

Hindustan Motors Ltd, Uttarpara

Indian Telephone Industries Ltd, Bangalore

Ministry of Defence (DGI), Department of
Defence Production

Mukand Iron & Steel, Bombay

Ministry of Defence (R & D)

Textile Machinery Corporation Ltd, Belgharia

Indian Copper Information Centre, Calcutta

Directorate General of Technical Development

Murarka Engineering Works, New Delhi

Director General, ISI (*Ex-officio Member*)

Secretary

SHRI B. MUKHERJI

Deputy Director (Met), ISI

Indian Standard

CODE OF PRACTICE FOR PREPARATION OF METALLOGRAPHIC SPECIMENS

PART X TIN AND ITS ALLOYS AND THEIR EXAMINATION

0. F O R E W O R D

0.1 This Indian Standard (Part X) was adopted by the Indian Standards Institution on 31 December 1975, after the draft finalized by the Metallography and Heat-Treatment Sectional Committee had been approved by the Structural and Metals Division Council.

0.2 The primary object of metallographic examination is to reveal the constituents and the structure of metals and their alloys by means of a microscope. Because of diversity in available equipment, wide variety of problems encountered, and the personal element, this standard gives for the guidance of the metallographer only those practices which experience has shown are generally satisfactory.

0.3 This standard is being issued in parts. This part covers polishing, etching and examination of tin and its alloys. The other parts of this code are given on fourth cover page.

1. SCOPE

1.1 This standard (Part X) covers the polishing, etching and examination of tin and its alloys.

2. PREPARATION OF SPECIMENS

2.0 Recommended methods of selection, size, cutting, cleaning and mounting of metallographic specimens are outlined in Part I of this standard.

2.1 These metals are in a class with lead and its alloys and may advantageously be prepared similarly. Tin and its softer alloys may be prepared by microtoming, but the harder alloys may require one or two polishing steps before etching. Alternate polishing and etching is frequently desirable.

2.2 Specimens may be smoothed on a lathe with a tool having a sharp, smooth, cutting edge and large clearance, followed by polishing on emery papers from No. 0 to 000, lubricated with paraffin dissolved in kerosene. After the operation is completed on each paper, the specimen may be etched with hydrochloric acid (HCl) (10 to 20 percent), or other solution as required, for a short time to remove any metal that may have been flowed on the polished surface. The specimen is then polished on a broadcloth-covered wheel, using a solution of soap and levigated Alundum grain. The specimen is then again etched and finally polished on a second wheel covered with high-grade silk velvet using the same polishing medium as for the broadcloth. Alternate polishing and etching will be required to bring out the structure satisfactorily. (For details of grit numbers of abrasive papers, see IS : 715-1966* and IS : 2832-1964†.) A comparative chart of grit numbers of abrasive grains is given in Appendix A.

2.3 A solution of paraffin and kerosene may be prepared by dissolving 100 g of paraffin in 200 ml of warm kerosene. The solution of soap and levigated Alundum grain may be prepared as follows:

5 g of Alundum grain (Norton size No. 600 grain) added to 300 ml of water. After thorough agitation, the mixture is permitted to stand for 15 minutes, whereupon the supernatant suspension is decanted. To this decanted suspension 40 g of soap are added and the mixture heated until the soap is dissolved. Both mixtures are nearly solid at room temperature, so that it is necessary to use them warm. To remove the paraffin before etching, the samples are washed in warm kerosene and the kerosene is removed by washing the specimen with soap and water. The soap film may be dried on, or removed, in a strong stream of warm water.

2.4 The preparation of cross sections of tin plate so as to show, with the microscope, the tin coating and its structure, requires very careful polishing and support of the edge of the specimen. Bakelite lacquer with cellophane has been found to afford satisfactory edge support, and polishing with alumina on broadcloth and velvet has given good results.

3. ETCHING REAGENTS

3.1 In Table 1 are given the etching reagents commonly recommended for tin and its alloys.

3.2 After etching, the specimen is immediately and thoroughly washed with distilled water, followed by rinsing in a suitable medium (alcohol, acetone, etc) and drying to avoid staining. The specimen should be preserved, if required, in a desiccator.

*Specification for coated abrasives, glue bond (*second revision*).

†Specification for waterproof silicon carbide paper.

TABLE 1 ETCHING REAGENTS FOR TIN AND ITS ALLOYS

(Clause 3.1)

SL No.	ETCHING REAGENT	COMPOSITION*	REMARKS	USE
(1)	(2)	(3)	(4)	(5)
i)	Nital	HNO ₃ 2 to 5 ml Ethyl alcohol 95 to 98 ml	Swab or immerse for several minutes	Tin-cadmium or tin-iron alloys
ii)	Potassium dichromate	Acidified dilute solution	—	Tin-cadmium alloys
iii)	Mixed acids in glycerine	a) HNO ₃ 1 part Acetic acid 1 part Glycerine 8 parts b) HNO ₃ 1 part Acetic acid 3 parts Glycerine 5 parts	Immerse $\frac{1}{2}$ to 10 minutes at 38 to 42°C Same as for (a) above	a) Tin-lead alloys b) Pure tin
iv)	Hydrochloric acid	a) HCl b) HCl 10 to 20 ml H ₂ O 90 to 80 ml c) HCl 10 ml H ₂ O 90 ml	a) Immerse for several seconds b) Immerse $\frac{1}{2}$ to 5 minutes following (a) c) Electrolytic etch at low current density	a) To remove surface flow b) Follows (a) c) Tin-iron alloys
v)	Ferric chloride	FeCl ₃ 10 g HCl 2 ml H ₂ O 95 ml	Immerse for $\frac{1}{2}$ to 5 minutes at room temperature	Microetching of tin-rich babbitt metals
vi)	Acid ferric chloride	FeCl ₃ 2 g HCl 5 ml H ₂ O 30 ml Ethyl alcohol 60 ml	Alternate polish and etch	For block tin
vii)	Nitric and hydrofluoric acid in glycerin	HNO ₃ 1 drop HF 2 drops Glycerine 25 ml	Etch for 1 minute at 20 to 27°C	For the tin coating on tin-plate
viii)	Ammonium polysulphide	Concentrated solution	Immerse for 20 to 30 minutes at room temperature	Macroetching of tin-rich babbitt metals

NOTE — Solutions of silver nitrate or 10 percent nitric acid plus 5 percent chromic acid are also occasionally used.

*The use of concentrated reagents is intended, unless otherwise specified.

APPENDIX A

(Clause 2.2)

COMPARATIVE CHART OF GRIT NUMBERS (APPROXIMATE) OF ABRASIVE GRAINS

ALUMINIUM OXIDE, SILICON CARBIDE AND GARNET		FLINT		GLASS		CORUNDUM		EMERY		TRADE DESIGNATION
IS Grit Number	B.S. Grade Number	IS Grit Number	B.S. Grade Number	IS Grit Number	B.S. Grade Number	IS Grit Number	B.S. Grade Number	IS Grit Number	B.S. Grade Number	
14	14	—	—	—	—	—	—	—	—	—
16	16	—	—	—	—	—	—	—	—	—
24	24	24	3	24	3	24	—	24	—	Extra Coarse
30	30	30	2½	30	2½	30	—	30	—	Extra Coarse
36	36	36	2	36	—	36	—	36	3	Coarse
40	46	40	1½	40	S2	40	—	40	2½	Coarse
50	54	50	1	50	M2	50	—	50	2	Medium Coarse
60	60	60	½	60	—	60	—	60	1½	Medium
80	80	80	—	80	—	80	—	80	1	Medium
100	100	100	0	100	F2	100	—	100	F	Medium Fine
120	120	120	00	120	1½	120	—	120	FF	Fine
150	150	150	—	150	1	150	—	150	—	Fine
180	180	180	—	180	0	180	—	180	0	Extra Fine
220	220	—	—	—	—	—	—	—	—	—

NOTE — Grits 240 and finer come under the sub-sieve range and as limits for these cannot be set on common silk test sieves, the grain sizes shall conform to general commercial grading, and it is recommended that the sedimentation process be adopted for their analysis.

INDIAN STANDARDS ON METALLOGRAPHY AND HEAT TREATMENT

IS:

- 2756-1965 Method for estimating the average grain size of wrought copper and copper base alloys
- 2853-1964 Method for determining the austenitic grain size of steel
- 4075-1967 Methods of macro-streak flaw test for steel
- 4163-1967 Determination of inclusion content in steel by microscopic method
- 4748-1968 Method for estimating average grain size of metals
- 6396-1971 Methods of measuring decarburized depth of steel
- 6416-1971 Methods of measuring case depth of steel
- 7739 Code of practice for preparation of metallographic specimens:
 - (Part I)-1975 General features
 - (Part II)-1975 Electrolytic polishing
 - (Part III)-1975 Aluminium and its alloys and their examination
 - (Part IV)-1975 Copper and its alloys and their examination
 - (Part V)-1975 Iron and steel and their examination
 - (Part VI)-1975 Lead and its alloys and their examination
 - (Part VII)-1975 Magnesium and its alloys and their examination
 - (Part VIII)-1975 Nickel and its alloys and their examination
 - (Part IX)-1975 Gold, silver, platinum, palladium and their alloys and their examination
 - (Part XI)-1975 Zinc and its alloys and their examination

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephone : 27 01 31 (20 lines)

Telegrams : Manaksanstha

Regional Offices:

		Telephone
Western : Novelty Chambers, Grant Road	BOMBAY 400007	37 97 29
Eastern : 5 Chowringhee Approach	CALCUTTA 700072	23-08 02
Southern : C.I.T. Campus, Adyar	MADRAS 600020	41 24 42

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur	AHMADABAD 380001	2 03 91
'F' Block, Unity Bldg, Narasimharaja Square	BANGALORE 560002	2 76 49
Ahimsa Bldg, SCO 82-83, Sector 17C	CHANDIGARH 160017	2 83 20
5-8-56/57 Nampally Station Road	HYDERABAD 500001	4 57 11
117/418B Sarvodaya Nagar	KANPUR 208005	82 72
B.C.I. Bldg (3rd Floor), Gandhi Maidan East	PATNA 800004	5 36 55
Hantex Bldg (2nd Floor), Rly Station Road	TRIVANDRUM 695001	32 27